

Safety data sheet

according to GB/T 16483-2008, GB/T 17519-2013

Printing date 02.03.2023

Version number 04-02

Revision: 02.03.2023

1 Identification of the substance/mixture and of the company/undertaking

Product identifier

Trade name: **LUCITE® 800 HousePaint**

Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture Coating agent

Uses advised against

This product is not suitable for uses other than those specified in the "Use of the substance/mixture". If your particular manner of use is not listed, please contact the creator of this safety data sheet.

Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Dörken Coatings GmbH & Co. KG
Wetterstr. 58
58313 Herdecke
Germany
www.doerkencoatings.de

Phone: +49 2330 63 243

Fax: +49 2330 63 100 243

Further information obtainable from: msds.coatings@doerken.de

Emergency telephone number: +86 532 8388 9090

2 Hazards identification

Classification of the substance or mixture



Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Acute 3 H402 Harmful to aquatic life.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

Label elements

GHS label elements

The product is classified and labelled according to the Globally Harmonised System (GHS).

Hazard pictograms



GHS07

Signal word Warning

Hazard-determining components of labelling:

2-methyl-2H-isothiazol-3-one

2-octyl-2H-isothiazol-3-one

(Contd. on page 2)

Safety data sheet

according to GB/T 16483-2008, GB/T 17519-2013

Printing date 02.03.2023

Version number 04-02

Revision: 02.03.2023

Trade name: LUCITE® 800 HousePaint

(Contd. of page 1)

Hazard statements

May cause an allergic skin reaction.
Harmful to aquatic life with long lasting effects.

Precautionary statements**Prevention**

Avoid breathing dust/fume/gas/mist/vapours/spray.
Contaminated work clothing should not be allowed out of the workplace.
Avoid release to the environment.
Wear protective gloves.

Response

IF ON SKIN: Wash with plenty of water.
Take off contaminated clothing and wash it before reuse.
If skin irritation or rash occurs: Get medical advice/attention.

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

Other hazards**Results of PBT and vPvB assessment**

PBT: Not applicable.
vPvB: Not applicable.

3 Composition/information on ingredients**Chemical characterisation: Mixtures**

Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:

55934-93-5	[(butoxymethylethoxy)methylethoxy]propan-1-ol Acute Tox. 5, H303; Acute Tox. 5, H313	<2.5%
2682-20-4	2-methyl-2H-isothiazol-3-one Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 2, H330; Skin Corr. 1B, H314; Eye Dam. 1, H318; Aquatic Acute 1, H400 (M=10); Aquatic Chronic 1, H410 (M=1); Skin Sens. 1A, H317 Specific concentration limit: Skin Sens. 1A; H317: C ≥ 0.0015 %	≥0.0015-<0.025%
26530-20-1	2-octyl-2H-isothiazol-3-one Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 2, H330; Skin Corr. 1A, H314; Eye Dam. 1, H318; Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410 (M=100); Skin Sens. 1A, H317 Specific concentration limit: Skin Sens. 1A; H317: C ≥ 0.0015 %	≥0.0025-<0.025%
3811-73-2	pyridine-2-thiol 1-oxide, sodium salt Acute Tox. 3, H311; Acute Tox. 3, H331; STOT RE 1, H372; Aquatic Acute 1, H400 (M=100); Aquatic Chronic 2, H411; Acute Tox. 4, H302; Skin Irrit. 2, H315; Serious eye damage/irritation – Category 2A, H319; Skin Sens. 1, H317	≥0.0025-<0.025%

(Contd. on page 3)

CN

Safety data sheet

according to GB/T 16483-2008, GB/T 17519-2013

Printing date 02.03.2023

Version number 04-02

Revision: 02.03.2023

Trade name: LUCITE® 800 HousePaint

(Contd. of page 2)

Additional information: For the wording of the listed hazard phrases refer to section 16.

4 First aid measures

Description of first aid measures**General information:**

In all cases of doubt, or when symptoms persist, seek medical advice.

Soiled, soaked clothes immediately take off.

Never give anything by mouth to an unconscious person.

After inhalation:

Supply fresh air; consult doctor in case of complaints.

In case of unconsciousness place patient stably in side position for transportation.

After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation or rash occurs: Get medical advice/attention.

Take off immediately all contaminated clothing and wash it before reuse.

After eye contact:

Remove contact lenses. Keep eye lids open and rinse plentifully for at least 10 minutes with clean running water. Subsequently consult an ophthalmologist.

In case of troubles or persistent symptoms, consult an ophthalmologist.

After swallowing:

Rinse mouth thoroughly with water.

Drink plenty of water and provide fresh air. Call for a doctor immediately.

Information for doctor:**Most important symptoms and effects, both acute and delayed** Allergic reactions**Indication of any immediate medical attention and special treatment needed** Symptomatic treatment.

5 Firefighting measures

Extinguishing media**Suitable extinguishing agents:**

Extinguishing powder, foam, carbon dioxide.

Use fire extinguishing methods suitable to surrounding conditions.

For safety reasons unsuitable extinguishing agents: Water with full jet**Special hazards arising from the substance or mixture**Fire will produce dangerous decomposition products like dense, black smoke, carbon dioxide (CO₂), carbon monoxide (CO) and nitrogen oxides (NO_x). Inhalation may cause serious health damage.

Under certain fire conditions, traces of other toxic gases cannot be excluded.

Advice for firefighters**Protective equipment:**

Wear self-contained respiratory protective device.

Wear fully protective suit.

(Contd. on page 4)

Safety data sheet

according to GB/T 16483-2008, GB/T 17519-2013

Printing date 02.03.2023

Version number 04-02

Revision: 02.03.2023

Trade name: LUCITE® 800 HousePaint

(Contd. of page 3)

Additional information

Collect contaminated fire fighting water separately. It must not enter the sewage system.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.
Avoid contact with skin and eyes.

Environmental precautions:

Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Keep contaminated washing water and dispose of appropriately.

Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose of the material collected according to regulations.

Reference to other sections

See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

Handling:**Precautions for safe handling**

Avoid prolonged, intensive skin contact and contact with the eyes.
Avoid the handling of incompatible substances and mixtures. Incompatible substances: see section 10.5

Information about fire - and explosion protection: No special measures required.**Conditions for safe storage, including any incompatibilities****Storage:****Requirements to be met by storerooms and receptacles:**

Make sure spills can be contained, e.g. in sump pallets.
Protect from frost, heat and direct sunlight. Keep tightly closed, cool and dry.

Information about storage in one common storage facility: Store away from foodstuffs.**Further information about storage conditions:** None.**Storage class:** 12**Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

Additional information about design of technical facilities:

Ensure a good ventilation. This can be achieved by local exhaustion or general exhaust air.

(Contd. on page 5)

Safety data sheet

according to GB/T 16483-2008, GB/T 17519-2013

Printing date 02.03.2023

Version number 04-02

Revision: 02.03.2023

Trade name: LUCITE® 800 HousePaint

(Contd. of page 4)

Control parameters**Ingredients with limit values that require monitoring at the workplace:** No data.**Additional information:** The lists valid during the making were used as basis.**Exposure controls** Provide good ventilation and/or an exhaust system in the work area.**Personal protective equipment:****General protective and hygienic measures:**

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Immediately remove all soiled and contaminated clothing

Do not eat, drink, smoke or sniff while working.

Use skin protection cream for skin protection.

Respiratory protection:

Use always breathing protection with splashing medium.

Use combination filter type A(-P2) according to EN 141.

Protection of hands:

Work with gloves. Gloves must be inspected for damage before use. Defective or damaged gloves must not be used. Gloves must satisfy the specifications of EC directive 89/686/EWG and standard EN 374.

It is recommended to use long gloves to minimize contact by splashing.

Material of gloves

Nitrile rubber

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection:

Wear protective goggles to protect against splashing.

Have eye wash bottle or eye rinse ready at work place.

Body protection: Impervious protective clothing**9 Physical and chemical properties****Information on basic physical and chemical properties****General Information****Appearance:****Form:** Fluid**Colour:** Different according to colouring**Odour:** Weak after glycol ethers

(Contd. on page 6)

CN

Safety data sheet

according to GB/T 16483-2008, GB/T 17519-2013

Printing date 02.03.2023

Version number 04-02

Revision: 02.03.2023

Trade name: LUCITE® 800 HousePaint

(Contd. of page 5)

Odour threshold:	For mixtures not applicable.
pH-value at 20 °C:	8.4-9.2
Change in condition Melting point/Freezing point: Initial boiling point and boiling range:	Not security-related. 100 °C
Flash point:	Not applicable.
Flammability (solid, gas):	Not applicable.
Ignition temperature:	Not applicable.
Decomposition temperature:	For mixtures not applicable.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product does not present an explosion hazard.
Explosion limits: Lower: Upper:	Not determined. Not determined.
Oxidising properties	In its condition as supplied, the product is neither flammable nor oxidising.
Vapour pressure at 20 °C: Density at 20 °C:	23 hPa 1.22-1.45 g/cm ³
Vapour density	Not applicable.
Evaporation rate	For mixtures not applicable.
Solubility in / Miscibility with water: polar solvents: non-polar solvents:	Miscible / waterdilutable. Partly miscible. Not miscible or difficult to mix.
Partition coefficient: n-octanol/water:	For mixtures not applicable.
Viscosity:	Not security-related.
Other information	No further relevant information available.

10 Stability and reactivity**Reactivity**

No dangerous reactions are known.
No further relevant information available.

Chemical stability Product is stable under normal storage conditions.

(Contd. on page 7)

Safety data sheet

according to GB/T 16483-2008, GB/T 17519-2013

Printing date 02.03.2023

Version number 04-02

Revision: 02.03.2023

Trade name: LUCITE® 800 HousePaint

(Contd. of page 6)

Possibility of hazardous reactions

No dangerous reactions known.

No dangerous reactions are known.

Conditions to avoid No further relevant information available.**Incompatible materials:** strong oxidizing agents**Hazardous decomposition products:**

In case of fire arise: smoke and carbon oxides. Under certain fire conditions tracks of other toxic products can not be excluded.

11 Toxicological information**Information on toxicological effects****Acute toxicity****LD/LC50 values relevant for classification:**

The quoted data are literature values and/or manufacturer/supplier data.

Specific symptoms in biological assay:**Skin corrosion/irritation** May cause irritations.**Serious eye damage/irritation** May cause irritations.**Respiratory or skin sensitisation** No sensitising effects known.**Additional toxicological information:** Carcinogenic.**CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**

The product is not classified as carcinogenic, mutagenic or toxic to reproduction (CMR properties).

Aspiration hazard

The mixture contains no or only small amounts of materials which are classified as an aspiration hazard. It can therefore be assumed that the mixture is not an aspiration hazard.

12 Ecological information**Toxicity****Aquatic toxicity:** Harmful to aquatic life with long lasting effects.**Persistence and degradability** No further relevant information available.**Behaviour in environmental systems:****Bioaccumulative potential** No further relevant information available.**Mobility in soil** No further relevant information available.**Ecotoxicological effects:****Other information:**

This product contains the following priority substance in accordance with Annex X of the EU Water Directive 2000/60/EC:

330-54-1 Diuron

General notes: Do not allow product to reach ground water, water course or sewage system.

(Contd. on page 8)

Safety data sheet

according to GB/T 16483-2008, GB/T 17519-2013

Printing date 02.03.2023

Version number 04-02

Revision: 02.03.2023

Trade name: LUCITE® 800 HousePaint

(Contd. of page 7)

Results of PBT and vPvB assessment

This product does not contain relevant substances that have been assessed as persistent, bioaccumulative and toxic (PBT) or as very persistent and very bioaccumulative (vPvB).

PBT: Not applicable.**vPvB:** Not applicable.**Other adverse effects** No further relevant information available.**13 Disposal considerations****Waste treatment methods****Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Must be specially treated adhering to official regulations.

14 Transport information**UN-Number**

ADR, ADN, IMDG, IATA

Void

UN proper shipping name

ADR, ADN, IMDG, IATA

Void

Transport hazard class(es)

ADR, ADN, IMDG, IATA

Class

Void

Packing group

ADR, IMDG, IATA

Void

Environmental hazards:

Not applicable.

Special precautions for user

Not applicable.

Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable.

UN "Model Regulation":

Void

15 Regulatory information**Safety, health and environmental regulations/legislation specific for the substance or mixture
GHS label elements**

The product is classified and labelled according to the Globally Harmonised System (GHS).

(Contd. on page 9)

Safety data sheet

according to GB/T 16483-2008, GB/T 17519-2013

Printing date 02.03.2023

Version number 04-02

Revision: 02.03.2023

Trade name: LUCITE® 800 HousePaint

(Contd. of page 8)

Hazard pictograms

GHS07

Signal word Warning**Hazard-determining components of labelling:**

2-methyl-2H-isothiazol-3-one

2-octyl-2H-isothiazol-3-one

Hazard statements

May cause an allergic skin reaction.

Harmful to aquatic life with long lasting effects.

Precautionary statements**Prevention**

Avoid breathing dust/fume/gas/mist/vapours/spray.

Contaminated work clothing should not be allowed out of the workplace.

Avoid release to the environment.

Wear protective gloves.

Response

IF ON SKIN: Wash with plenty of water.

Take off contaminated clothing and wash it before reuse.

If skin irritation or rash occurs: Get medical advice/attention.

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

Directive 2012/18/EU**Named dangerous substances - ANNEX I** None of the ingredients is listed.**National regulations:****Information about limitation of use:**

Observe employment restrictions concerning young persons.

Observe employment restrictions for expectant or nursing mothers.

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.**16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

The given conditions of work of the user extract themselves from our knowledge and control. The product/the preparation may be used without written permission for no other use, than the mentioned intended purpose. The user is responsible for the observance of all necessary legal instructions.

This Safety Data Sheet replaces all previous versions. With the newest version in each case, the preceding Safety Data Sheets are set out of strength.

For further information please consult the "Technical Data Sheet".

(Contd. on page 10)

Safety data sheet

according to GB/T 16483-2008, GB/T 17519-2013

Printing date 02.03.2023

Version number 04-02

Revision: 02.03.2023

Trade name: LUCITE® 800 HousePaint

(Contd. of page 9)

Misuse may cause damage to health and environment.

Contact:**Abbreviations and acronyms:**

Acute Tox. 3: Acute toxicity – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Acute Tox. 5: Acute toxicity – Category 5

Acute Tox. 2: Acute toxicity – Category 2

Skin Corr. 1A: Skin corrosion/irritation – Category 1A

Skin Corr. 1B: Skin corrosion/irritation – Category 1B

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Serious eye damage/irritation – Category 2A: Serious eye damage/eye irritation – Category 2A

Skin Sens. 1: Skin sensitisation – Category 1

Skin Sens. 1A: Skin sensitisation – Category 1A

STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

Aquatic Acute 3: Hazardous to the aquatic environment - acute aquatic hazard – Category 3

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

Sources

- Regulation 1907/2006/EC (REACH-Regulation)

- Regulation 1272/2008/EC (CLP-Regulation)

*** Data compared to the previous version altered.**