

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.09.2020

Version number 02-00

Revision: 01.09.2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: DELTA® AntiCor DTS Verdünnung S

Safety data sheet number: 07-071904398401

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture Thinner, Diluent

Uses advised against

This product is not suitable for uses other than those specified in the "Use of the substance/mixture". If your particular manner of use is not listed, please contact the creator of this safety data sheet.

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Dörken Coatings GmbH & Co. KG
 formerly: CD-Color GmbH & Co. KG
 Wetterstr. 58
 58313 Herdecke
 Germany
 www.doerkencoatings.de

Phone: +49 2330 63 243

Fax: +49 2330 63 100 243

Further information obtainable from: msds.coatings@doerken.de

1.4 Emergency telephone number:

Australia: 61-290372994

United Kingdom: 44-870-8200418 and 44-2038073798

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 3 H226

Flammable liquid and vapour.



GHS08 health hazard

STOT RE 2 H373

May cause damage to organs through prolonged or repeated exposure.

Asp. Tox. 1 H304

May be fatal if swallowed and enters airways.



GHS07

Skin Irrit. 2 H315

Causes skin irritation.

Eye Irrit. 2 H319

Causes serious eye irritation.

(Contd. on page 2)

DE/EN

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.09.2020

Version number 02-00

Revision: 01.09.2020

Trade name: DELTA® AntiCor DTS Verdünnung S

(Contd. of page 1)

 STOT SE 3 H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

2.2 Label elements
Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms


GHS02 GHS07 GHS08

Signal word Danger

Hazard-determining components of labelling:

xylene (mix)

ethylbenzene

n-Butyl acetate

Hazard statements

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P240 Ground and bond container and receiving equipment.

P260 Do not breathe mist/vapours/spray.

P280 Wear protective gloves / eye protection / face protection.

P301+P310 IF SWALLOWED: Immediately call a doctor.

P321 Specific treatment (see on this label).

P331 Do NOT induce vomiting.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P362+P364 Take off contaminated clothing and wash it before reuse.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3 Other hazards

Vapours of the product are heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.

Vapours can form explosive mixtures with air.

In case of inhalation: Higher doses may lead to a narcotic effect.

Results of PBT and vPvB assessment
PBT: Not applicable.

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.09.2020

Version number 02-00

Revision: 01.09.2020

Trade name: DELTA® AntiCor DTS Verdünnung S

(Contd. of page 2)

vPvB: Not applicable.

SECTION 3: Composition/information on ingredients
3.2 Mixtures
Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:

CAS: 108-65-6 EINECS: 203-603-9 Reg.nr.: 01-2119475791-29-xxxx	2-Methoxy-1-methylethyl acetate Flam. Liq. 3, H226	25-50%
CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29-xxxx	n-Butyl acetate Flam. Liq. 3, H226; STOT SE 3, H336	25-50%
CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32-xxxx	xylene (mix) Flam. Liq. 3, H226; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	25-50%
CAS: 100-41-4 EINECS: 202-849-4 Reg.nr.: 01-2119489370-35-xxxx	ethylbenzene Flam. Liq. 2, H225; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H332; Aquatic Chronic 3, H412	10%

Additional information:

All hydrocarbons used comply with note P (less than 0.1% benzene) of the CLP regulation.
For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures
4.1 Description of first aid measures
General information:

In all cases of doubt, or when symptoms persist, seek medical advice.

Soiled, soaked clothes immediately take off.

Never give anything by mouth to an unconscious person.

After inhalation:

Supply fresh air; consult doctor in case of complaints.

In case of unconsciousness place patient stably in side position for transportation.

After skin contact:

Wash with plenty of soap and water.

If skin irritation continues, consult a doctor.

After eye contact:

Remove contact lenses. Keep eye lids open and rinse plentifully for at least 10 minutes with clean running water. Subsequently consult an ophthalmologist.

In case of troubles or persistent symptoms, consult an ophthalmologist.

After swallowing:

Rinse mouth thoroughly with water.

Risk of aspiration!

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.09.2020

Version number 02-00

Revision: 01.09.2020

Trade name: DELTA® AntiCor DTS Verdünnung S

(Contd. of page 3)

Do not induce vomiting; call for medical help immediately.

4.2 Most important symptoms and effects, both acute and delayed

Inhalation may cause an irritating effect to mucous membranes.

After eye contact: May cause irritations.

Headache, dizziness, numbness, sickness/nausea, tiredness, stunning effect, dry skin, allergic reactions.

Hazards

When swallowed and vomited immediately, aspiration into the lungs may occur resulting in chemical pneumonia or suffocation.

4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

SECTION 5: Firefighting measures**5.1 Extinguishing media****Suitable extinguishing agents:**

Extinguishing powder, foam, carbon dioxide.

Use fire extinguishing methods suitable to surrounding conditions.

For safety reasons unsuitable extinguishing agents: Water with full jet

5.2 Special hazards arising from the substance or mixture

Flammable liquid and vapour.

Can form explosive gas-air mixtures.

The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.

Fire will produce dangerous decomposition products like dense, black smoke, carbon dioxide (CO₂), carbon monoxide (CO) and nitrogen oxides (NO_x). Inhalation may cause serious health damage.

Under certain fire conditions, traces of other toxic gases cannot be excluded.

5.3 Advice for firefighters**Protective equipment:**

Wear self-contained respiratory protective device.

Wear fully protective suit.

Additional information

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

Keep away from ignition sources and ensure a well-ventilated room. Do not inhale fumes.

Avoid contact with skin and eyes.

6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.09.2020

Version number 02-00

Revision: 01.09.2020

Trade name: DELTA® AntiCor DTS Verdünnung S

(Contd. of page 4)

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose of the material collected according to regulations.

6.4 Reference to other sections

See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage**7.1 Precautions for safe handling**

Avoid the formation of ignitable and explosion- hazardous solution vapours.
Ensure good ventilation/exhaustion at the workplace.
Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).
Material can become charged electrostatically. Anti-static clothing including shoes are recommended.
Avoid contact with skin and eyes as well as inhalation of vapours.
Avoid the handling of incompatible substances and mixtures. Incompatible substances: see section 10.5

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Solvent fumes are heavier than air and spread over the ground. Fumes can form an explosive mixture with air.

7.2 Conditions for safe storage, including any incompatibilities**Storage:****Requirements to be met by storerooms and receptacles:**

Make sure spills can be contained, e.g. in sump pallets.
Protect from frost, heat and direct sunlight. Keep tightly closed, cool and dry.

Information about storage in one common storage facility:

Note the rules for common storage in accordance with TRGS 510 - "Storage of hazardous substances in transportable containers".

Store away from foodstuffs.

Further information about storage conditions: None.

Storage class: 3

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection**Additional information about design of technical facilities:**

Ensure a good ventilation. This can be achieved by local exhaustion or general exhaust air.

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.09.2020

Version number 02-00

Revision: 01.09.2020

Trade name: DELTA® AntiCor DTS Verdünnung S

(Contd. of page 5)

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

108-65-6 2-Methoxy-1-methylethyl acetate

AGW (Germany)	Long-term value: 270 mg/m ³ , 50 ppm 1(I);DFG, EU, Y
---------------	--

123-86-4 n-Butyl acetate

AGW (Germany)	Long-term value: 300 mg/m ³ , 62 ppm 2(I);AGS, Y
---------------	--

1330-20-7 xylene (mix)

AGW (Germany)	Long-term value: 440 mg/m ³ , 100 ppm 2(II);DFG, EU, H
---------------	--

100-41-4 ethylbenzene

AGW (Germany)	Long-term value: 88 mg/m ³ , 20 ppm 2(II);DFG, H, Y, EU
---------------	---

Regulatory information AGW (Germany): TRGS 900

DNELs

123-86-4 n-Butyl acetate

Inhalative	DNEL1	480 mg/m ³ (71)
------------	-------	----------------------------

1330-20-7 xylene (mix)

Dermal	DNEL3	180 mg/kg bw/day (71)
Inhalative	DNEL1	77 mg/m ³ (71)
	DNEL2	289 mg/m ³ (71)
	DNEL6	289 mg/m ³ (71)

100-41-4 ethylbenzene

Dermal	DNEL3	180 mg/kg bw/day (71)
Inhalative	DNEL1	77 mg/m ³ (71)
	DNEL6	293 mg/m ³ (71) (irritation (respiratory tract))

PNECs

123-86-4 n-Butyl acetate

PNEC	180 µg/l (72)
	18 µg/l (73)
	90.3 µg/kg dw (75)
	35.6 mg/l (76)
	98.1 µg/kg dw (77)
	981 µg/kg dw (78)
	360 µg/l (79)

1330-20-7 xylene (mix)

PNEC	0.327 mg/l (72)
	0.327 mg/l (73)

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.09.2020

Version number 02-00

Revision: 01.09.2020

Trade name: DELTA® AntiCor DTS Verdünnung S

(Contd. of page 6)

	2.31 mg/kg dw (75) 6.58 mg/l (76) 12.46 mg/kg dw (77) 12.46 mg/kg dw (78) 0.327 mg/l (79)
--	---

100-41-4 ethylbenzene

PNEC	100 µg/l (72) 10 µg/l (73) 2.68 mg/kg dw (75) 9.6 mg/l (76) 1.37 mg/kg dw (77) 2.68 mg/kg dw (78) 100 µg/l (79)
------	---

Ingredients with biological limit values:
1330-20-7 xylene (mix)

BGW (Germany)	1.5 mg/l Untersuchungsmaterial: Vollblut Probennahmezeitpunkt: Expositionsende bzw. Schichtende Parameter: Xylol
	2 g/l Untersuchungsmaterial: Urin Probennahmezeitpunkt: Expositionsende bzw. Schichtende Parameter: Methylhippur-(Tolur-)Säure

100-41-4 ethylbenzene

BGW (Germany)	300 mg/l Untersuchungsmaterial: Urin Probennahmezeitpunkt: Expositionsende bzw. Schichtende Parameter: Mandelsäure plus Phenoxyglyxylsäure
---------------	---

Regulatory information BGW (Germany): TRGS 903

Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls Provide good ventilation and/or an exhaust system in the work area.

Personal protective equipment:
General protective and hygienic measures:

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Immediately remove all soiled and contaminated clothing

Store protective clothing separately.

Do not eat, drink, smoke or sniff while working.

Use skin protection cream for skin protection.

Respiratory protection:

Use always breathing protection with splashing medium.

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.09.2020

Version number 02-00

Revision: 01.09.2020

Trade name: DELTA® AntiCor DTS Verdünnung S

(Contd. of page 7)

Use combination filter type A(-P2) according to EN 141.

Protection of hands:

Work with gloves. Gloves must be inspected for damage before use. Defective or damaged gloves must not be used. Gloves must satisfy the specifications of EC directive 89/686/EWG and standard EN 374.

Material of gloves

Multi-layer glove - PE / EVAL / PE

(PE = polyethylene, EVAL = ethylene-vinyl alcohol copolymer)

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection:

Tightly sealed safety goggles are to be worn during all work, in accordance with EN 166.

Have eye wash bottle or eye rinse ready at work place.

Professional Cooperative Rules - BGR 192 Use of eye and face protection

Body protection: Solvent resistant protective clothing

SECTION 9: Physical and chemical properties
9.1 Information on basic physical and chemical properties
General Information
Appearance:

Form: Fluid
Colour: Colourless

Odour: Very Esther-like

Odour threshold: For mixtures not applicable.

pH-value: Not applicable to preparations which contain solvents.

Change in condition

Melting point/Freezing point: Not security-related.
Initial boiling point and boiling range: The specified boiling point corresponds to the manufacturer's specifications for the lowest boiling fraction.

Flash point: 25 °C

Flammability (solid, gas): Not applicable.

Ignition temperature: 315 °C
 The specified ignition temperature refers to the solvent manufacturer specifications.

(Contd. on page 9)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.09.2020

Version number 02-00

Revision: 01.09.2020

Trade name: DELTA® AntiCor DTS Verdünnung S

(Contd. of page 8)

Decomposition temperature:	For mixtures not applicable.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
Explosion limits:	
Lower:	1.0 Vol %
Upper:	10.8 Vol %
	The specified explosion limits refer to the solvent manufacturer specifications.
Oxidising properties	The product is flammable, although not oxidising.
Vapour pressure at 20 °C:	15 hPa The specified vapour pressure refers to the solvent manufacturer specifications.
Relative density	< 1,00
Vapour density	Not applicable.
Evaporation rate	For mixtures not applicable.
Solubility in / Miscibility with water:	Not miscible or difficult to mix.
polar solvents:	Not miscible or difficult to mix.
non-polar solvents:	Fully miscible.
Partition coefficient: n-octanol/water:	For mixtures not applicable.
Viscosity:	< 60 s (20°C / ISO 2431 / 6 mm) < 20,5 mm ² /s (40°C)
9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

10.1 Reactivity Vapours can form explosive mixtures with air.

10.2 Chemical stability Product is stable under normal storage conditions.

10.3 Possibility of hazardous reactions

No dangerous reactions known.

No dangerous reactions are known.

10.4 Conditions to avoid Keep away from heat sources, sparks and open flames.

10.5 Incompatible materials: strong oxidizing agents

10.6 Hazardous decomposition products:

In case of fire arise: smoke and carbon oxides. Under certain fire conditions tracks of other toxic products can not be excluded.

DE/EN

(Contd. on page 10)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.09.2020

Version number 02-00

Revision: 01.09.2020

Trade name: DELTA® AntiCor DTS Verdünnung S

(Contd. of page 9)

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

The product is not tested as one of the above but rather is classified according to the conventional method (calculation procedure set out in the EU Regulation (EC) No 1272/2008) and according to the toxicological risks. See chapters 2 and 3 for detail.

LD/LC50 values relevant for classification:

The quoted data are literature values and/or manufacturer/supplier data.

ATE (Acute Toxicity Estimates)

Dermal	LD ₅₀	3333 mg/kg (rabbit)
Inhalative	LC ₅₀ / 4 h	15 mg/l

108-65-6 2-Methoxy-1-methylethyl acetate

Oral	LD ₅₀	> 5000 mg/kg (rat)
Dermal	LD ₅₀	> 5000 mg/kg (rabbit)
Inhalative	LC ₅₀ / 4 h	> 20 mg/l (rat)

123-86-4 n-Butyl acetate

Oral	LD ₅₀	10760 mg/kg (rat) (OECD 423)
Dermal	LD ₅₀	>14112 mg/kg (rabbit) (OECD 402)
Inhalative	LC ₅₀ / 4 h	23.4 mg/l (rat) (OECD 403)

1330-20-7 xylene (mix)

Oral	LD ₅₀	>2000 mg/kg (rat)
Dermal	LD ₅₀	>1000 mg/kg (rabbit)
Inhalative	LC ₅₀ / 4 h	>10 mg/l (rat)

100-41-4 ethylbenzene

Oral	LD ₅₀	3500 mg/kg (rat)
Dermal	LD ₅₀	> 5000 mg/kg (rabbit)
Inhalative	LC ₅₀ / 4 h	1.5 mg/l (ATE)

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/irritation

Causes serious eye irritation.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

The product is not classified as carcinogenic, mutagenic or toxic to reproduction (CMR properties).

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

(Contd. on page 11)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.09.2020

Version number 02-00

Revision: 01.09.2020

Trade name: DELTA® AntiCor DTS Verdünnung S

(Contd. of page 10)

STOT-single exposure

May cause respiratory irritation. May cause drowsiness or dizziness.

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard

Due to the viscosity (see section 9), classification as an aspiration hazard is omitted.

May be fatal if swallowed and enters airways.

General notes:

Inhalation of solvent concentrations in excess of the OEL or MAK limit values can lead to health damage such as irritation of the mucous membranes and respiratory tract, damage to the kidneys and liver, and impairment of the central nervous system. Symptoms: headaches, dizziness, fatigue, muscle weakness, narcotic effect and, in exceptional cases, loss of consciousness. Prolonged or repeated contact with the product impairs the skin's natural lipid replenishment and causes the skin to dry out. The product can enter the body through the skin. Splashes of solvent may cause irritation to the eye and reversible damage.

SECTION 12: Ecological information
12.1 Toxicity
Aquatic toxicity:
108-65-6 2-Methoxy-1-methylethyl acetate
EC₅₀ / 48 h | 373 mg/l (Daphnia magna (big water flea)) (OECD 202)EC₅₀ / 72 h | > 1000 mg/l (Selenastrum capricornutum) (OECD 201)LC₅₀ / 96 h | > 100 mg/l (Oncorhynchus mykiss (rainbow trout)) (OECD 203)
123-86-4 n-Butyl acetate
EC₅₀ / 48 h | 44 mg/l (Daphnia magna (big water flea))EC₅₀ / 72 h | 647.7 mg/l (Pseudokirchneriella subcapitata)LC₅₀ / 96 h | 18 mg/l (Pimephales promelas (fathead minnow)) (OECD 203)
1330-20-7 xylene (mix)
LC₅₀ / 96 h | 13.5 mg/l (fish)
100-41-4 ethylbenzene
EC₅₀ / 48 h | 2.1 mg/l (Daphnia magna (big water flea))EC₅₀ / 96 h | 3.6 mg/l (algae)LC₅₀ / 96 h | 12.1 mg/l (Pimephales promelas (fathead minnow))
12.2 Persistence and degradability
123-86-4 n-Butyl acetate

OECD 301D Closed Bottle Test | 83 % (17) (28 d)

12.3 Bioaccumulative potential
123-86-4 n-Butyl acetate

OECD 117 Log Kow (HPLC method) | 2.3 (n-octanol/water)

(Contd. on page 12)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.09.2020

Version number 02-00

Revision: 01.09.2020

Trade name: DELTA® AntiCor DTS Verdünnung S

(Contd. of page 11)

1330-20-7 xylene (mix)

Partition Coefficient log Pow	3.15 (n-octanol/water)
-------------------------------	------------------------

12.4 Mobility in soil No further relevant information available.

Ecotoxicological effects:
Behaviour in sewage processing plants:
123-86-4 n-Butyl acetate

EC ₅₀	356 mg/l (bacteria) (Tetrahymena; 40 h)
------------------	---

12.5 Results of PBT and vPvB assessment

This product does not contain relevant substances that have been assessed as persistent, bioaccumulative and toxic (PBT) or as very persistent and very bioaccumulative (vPvB).

PBT: Not applicable.

vPvB: Not applicable.

12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations
13.1 Waste treatment methods
Recommendation

Special waste. Do not empty residuals into drain or WC; send to collection for problem waste. Do not dispose of with household waste.

European waste catalogue

08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances
HP 3	Flammable
HP 4	Irritant - skin irritation and eye damage
HP 5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity
HP 6	Acute Toxicity

Uncleaned packaging:
Recommendation:

Disposal must be made according to official regulations.

Not contaminated packages may be recycled.

Do not dispose of with household waste. Do not empty into drains.

Hand over receptacles/packages with remainders/leftovers to hazardous waste disposers or collection site for hazardous waste.

SECTION 14: Transport information
UN-Number
ADR, IMDG, IATA

UN1263

(Contd. on page 13)

DE/EN

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.09.2020

Version number 02-00

Revision: 01.09.2020

Trade name: DELTA® AntiCor DTS Verdünnung S

(Contd. of page 12)

14.2 UN proper shipping name

ADR 1263 PAINT RELATED MATERIAL
 IMDG, IATA PAINT RELATED MATERIAL

14.3 Transport hazard class(es)

ADR



Class 3 (F1) Flammable liquids.
 Label 3
 IMDG, IATA



Class 3 Flammable liquids.
 Label 3

Packing group

ADR, IMDG, IATA III

14.5 Environmental hazards: Not applicable.**14.6 Special precautions for user**

Warning: Flammable liquids.

Hazard identification number (Kemler code): 30**EMS Number:** F-E,S-E**Stowage Category** A**14.7 Transport in bulk according to Annex II of Marpol and the IBC Code**

Not applicable.

Transport/Additional information:

ADR

Limited quantities (LQ) 5L**Excepted quantities (EQ)** Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

Transport category 3**Tunnel restriction code** D/E

IMDG

Limited quantities (LQ) 5L**Excepted quantities (EQ)** Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

(Contd. on page 14)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.09.2020

Version number 02-00

Revision: 01.09.2020

Trade name: DELTA® AntiCor DTS Verdünnung S

(Contd. of page 13)

Remarks:	Not subject to the IMDG provisions when packed in receptacles not exceeding 30 L capacity.
-----------------	--

UN "Model Regulation":	UN 1263 PAINT RELATED MATERIAL, 3, III, (D/E)
-------------------------------	---

SECTION 15: Regulatory information
15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
Directive 2012/18/EU
Named dangerous substances - ANNEX I None of the ingredients is listed.

Seveso category P5c FLAMMABLE LIQUIDS

Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t

Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t

REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

National regulations:
Information about limitation of use:

Observe employment restrictions concerning young persons.

Observe employment restrictions for expectant or nursing mothers.

Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.

Labelling according to Regulation (EC) No 2004/42 Not applicable.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

The given conditions of work of the user extract themselves from our knowledge and control. The product/the preparation may be used without written permission for no other use, than the mentioned intended purpose. The user is responsible for the observance of all necessary legal instructions.

This Safety Data Sheet replaces all previous versions. With the newest version in each case, the preceding Safety Data Sheets are set out of strength.

For further information please consult the "Technical Data Sheet".
 Misuse may cause damage to health and environment.

Relevant phrases

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

(Contd. on page 15)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.09.2020

Version number 02-00

Revision: 01.09.2020

Trade name: DELTA® AntiCor DTS Verdünnung S

(Contd. of page 14)

H373 May cause damage to organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

Classification according to Regulation (EC) No 1272/2008

Flammable liquids	On basis of test data
Skin corrosion/irritation Serious eye damage/eye irritation Specific target organ toxicity (single exposure) Specific target organ toxicity (repeated exposure) Aspiration hazard	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

Abbreviations and acronyms:

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity - dermal – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

Sources

- Regulation 1907/2006/EC (REACH-Regulation)

- Regulation 1272/2008/EC (CLP-Regulation)