Page 1/11



Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 07.02.2025

Version number 06-02 (replaces version 06-01)

Revision: 07.02.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: LUCITE® 123 All-Top Satin

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture Coating agent

Uses advised against

This product is not suitable for uses other than those specified in the "Use of the substance/mixture". If your particular manner of use is not listed, please contact the creator of this safety data sheet.

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Dörken Coatings GmbH & Co. KG Wetterstr. 58 58313 Herdecke Germany www.doerkencoatings.de

Phone: +49 2330 63 243 Fax: +49 2330 63 100 243

Further information obtainable from: msds.coatings@doerken.de

1.4 Emergency telephone number:

Emergency CONTACT (24-Hour-Number): GBK GmbH +49 (0)6132-84463

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008 The product is not classified, according to the CLP regulation. 2.2 Label elements Labelling according to Regulation (EC) No 1272/2008 Void Hazard pictograms Void Signal word Void Hazard statements Void **Precautionary statements** Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No P210 smoking. Avoid breathing mist/vapours/spray. P261 Wear protective gloves. P280 P403+P233 Store in a well-ventilated place. Keep container tightly closed. P501 Dispose of contents/container in accordance with local/regional/national/international regulations. Additional information: EUH066 Repeated exposure may cause skin dryness or cracking. EUH210 Safety data sheet available on request.

(Contd. on page 2)



according to Regulation (EC) No 1907/2006, Article 31

Printing date 07.02.2025

Version number 06-02 (replaces version 06-01)

Revision: 07.02.2025

(Contd. of page 1)

Trade name: LUCITE® 123 All-Top Satin

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

2.3 Other hazards

Vapours of the product are heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.

Vapours can form explosive mixtures with air.

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:		
EC number: 918-481-9 Reg.nr.: 01-2119457273-39-xxxx	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2%	≥25-≤50%
Reg.11 01-2119457275-59-8888	Asp. Tox. 1, H304, EUH066	
CAS: 13463-67-7	Titanium dioxide	10-25%
EINECS: 236-675-5	Carc. 2, H351	
Reg.nr.: 01-2119489379-17-xxxx		
EC number: 927-632-8	Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, < 2%	1-10%
Reg.nr.: 01-2119457736-27-xxxx	aromatics	
	Asp. Tox. 1, H304, EUH066	
CAS: 55172-98-0	Barium neodecanoate	≥0-<2.5%
EINECS: 259-509-3	Acute Tox. 4, H302; Acute Tox. 4, H332	
Reg.nr.: 01-2119978984-12-xxxx		
EC number: 919-857-5 Reg.nr.: 01-2119463258-33-xxxx	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	≥0-<2.5%
	Flam. Liq. 3, H226; Asp. Tox. 1, H304; STOT SE 3, H336, EUH066	
CAS: 77-99-6	propylidynetrimethanol	<0.25%
EINECS: 201-074-9	Repr. 2, H361fd	
Reg.nr.: 01-2119486799-10-xxxx		

Additional information:

All hydrocarbons used comply with note P (less than 0.1% benzene) of the CLP regulation. For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures General information:

In all cases of doubt, or when symptoms persist, seek medical advice. Soiled, soaked clothes immediately take off.



according to Regulation (EC) No 1907/2006, Article 31

Printing date 07.02.2025

Version number 06-02 (replaces version 06-01)

Trade name: LUCITE® 123 All-Top Satin

(Contd. of page 2) Never give anything by mouth to an unconscious person. After inhalation: Supply fresh air; consult doctor in case of complaints. After skin contact: Wash with plenty of soap and water. After eye contact: Remove contact lenses. Keep eye lids open and rinse plentifully for at least 10 minutes with clean running water. Subsequently consult an ophthalmologist. In case of troubles or persistent symptoms, consult an opthalmologist. After swallowing: Rinse out mouth and then drink plenty of water. Seek immediate medical advice. 4.2 Most important symptoms and effects, both acute and delayed Prolonged/repetitive skin contact may cause skin defattening or dermatitis. Headache, dizziness, numbness, sickness/nausea, tiredness, stunning effect, dry skin, allergic reactions. 4.3 Indication of any immediate medical attention and special treatment needed Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents:

Extinguishing powder, foam, carbon dioxide. Use fire extinguishing methods suitable to surrounding conditions.

For safety reasons unsuitable extinguishing agents: Water with full jet

5.2 Special hazards arising from the substance or mixture

Can form explosive gas-air mixtures.

The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.

Fire will produce dangerous decomposition products like dense, black smoke, carbon dioxide (CO₂), carbon monoxide (CO) and nitrogen oxides (NOx). Inhalation may cause serious health damage. Under certain fire conditions, traces of other toxic gases cannot be excluded.

5.3 Advice for firefighters

Protective equipment:

Wear self-contained respiratory protective device. Wear fully protective suit.

Additional information

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Keep away from ignition sources and ensure a well-ventilated room. Do not inhale fumes. Avoid contact with skin and eyes.

(Contd. on page 4)



according to Regulation (EC) No 1907/2006, Article 31

Printing date 07.02.2025

Version number 06-02 (replaces version 06-01)

Revision: 07.02.2025

(Contd. of page 3)

Trade name: LUCITE® 123 All-Top Satin

6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose of the material collected according to regulations.

6.4 Reference to other sections

See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Avoid the formation of ignitible and explosion- hazardous solution vapours.

Ensure good ventilation/exhaustion at the workplace.

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

Material can become charged elektrostatically. Anti-static clothing including shoes are recommended.

Avoid contact with skin and eyes as well as inhalation of vapours.

Avoid the handling of incompatible substances and mixtures. Incompatible substances: see section 10.5

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Use explosion-proof apparatus / fittings and spark-proof tools.

Handle only outside or in explosion protected rooms.

Fumes can combine with air to form an explosive mixture.

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles:

Make sure spills can be contained, e.g. in sump pallets.

Protect from frost, heat and direct sunlight. Keep tightly closed, cool and dry.

Information about storage in one common storage facility:

Note the rules for common storage in accordance with TRGS 510 - "Storage of hazardous substances in transportable containers".

Store away from foodstuffs.

Further information about storage conditions: None.

Storage class: 10

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace: No data.

(Contd. on page 5)

Page 5/11



Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 07.02.2025

Version number 06-02 (replaces version 06-01)

Trade name: LUCITE® 123 All-Top Satin

(Contd. of page 4) Additional information: The lists valid during the making were used as basis. 8.2 Exposure controls Provide good ventilation and/or an exhaust system in the work area. Appropriate engineering controls Ensure a good ventilation. This can be achieved by local exhaustion or general exhaust air. Individual protection measures, such as personal protective equipment General protective and hygienic measures: Wash hands before breaks and at the end of work. Avoid contact with the eyes and skin. Immediately remove all soiled and contaminated clothing Do not eat, drink, smoke or sniff while working. Use skin protection cream for skin protection. **Respiratory protection:** Breathing protection is always required when spraying. Use combination filter A2(-P2) according to EN 14387. Hand protection Work with gloves. Gloves must be inspected for damage before use. Defective or damaged gloves must not be used. Gloves must satisfy the specifications of EC directive 89/686/EWG and standard EN 374. Material of gloves Nitrile rubber The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. Penetration time of glove material The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed. Eye/face protection Wear protective goggles to protect against splashing. Have eye wash bottle or eye rinse ready at work place. Professional Cooperative Rules - BGR 192 Use of eye and face protection Body protection: Solvent resistant protective clothing **SECTION 9: Physical and chemical properties** 9.1 Information on basic physical and chemical properties **General Information Physical state** Fluid Colour: Different according to colouring Odour: Weak after aliphatic hydrocarbons Odour threshold: Not applicable for mixtures.

(Contd. on page 6)

- DE/EN



Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 07.02.2025

Version number 06-02 (replaces version 06-01)

Revision: 07.02.2025

Trade name: LUCITE® 123 All-Top Satin

(Contd. of pag
Not security-related.
145-205 °C (Hydrocarbons, C9-C11, n-alkanes,
isoalkanes, cyclics, < 2% aromatics)
Not applicable.
0.6 Vol % (Hydrocarbons, C10-C13, n-alkanes,
isoalkanes, cyclics, < 2% aromatics)
7 Vol % (Hydrocarbons, C10-C13, n-alkanes,
isoalkanes, cyclics, < 2% aromatics)
62 °C
>200 °C (Hydrocarbons, C10-C13, n-alkanes,
isoalkanes, cyclics, < 2% aromatics)
For mixtures not applicable.
Mixture is non-soluble (in water).
> 90 s (20°C / DIN 53211 / 4 mm)
> 60 s (20°C / ISO 2431 / 6 mm)
> 20,5 mm²/s (40°C)
Not miscible or difficult to mix.
Not miscible or difficult to mix.
Fully miscible.
For mixtures not applicable.
3 hPa (Hydrocarbons, C9-C11, n-alkanes, isoalkane
cyclics, < 2% aromatics)
1.06-1.37 g/cm³
Not applicable.
Fluid
4
Product is not selfigniting.
Product is not explosive. However, formation of
explosive air/vapour mixtures are possible.
enprosive airvapour minitures are possible.
The product is flowmable, although not evidence
The product is flammable, although not oxidising.
For mixtures not applicable.
Void
Void Void
-



according to Regulation (EC) No 1907/2006, Article 31

Printing date 07.02.2025

Version number 06-02 (replaces version 06-01)

Revision: 07.02.2025

Trade name: LUCITE® 123 All-Top Satin

		(Contd. of page
Oxidising gases	Void	
Gases under pressure	Void	
Flammable liquids	Void	
Flammable solids	Void	
Self-reactive substances and mixtures	Void	
Pyrophoric liquids	Void	
Pyrophoric solids	Void	
Self-heating substances and mixtures	Void	
Substances and mixtures, which emit flamm	able	
gases in contact with water	Void	
Oxidising liquids	Void	
Oxidising solids	Void	
Organic peroxides	Void	
Corrosive to metals	Void	
Desensitised explosives	Void	

SECTION 10: Stability and reactivity

10.1 Reactivity Vapours can form explosive mixtures with air.

10.2 Chemical stability Product is stable under normal storage conditions.

10.3 Possibility of hazardous reactions No dangerous reactions known.

10.4 Conditions to avoid Keep away from heat sources, sparks and open flames.

10.5 Incompatible materials: strong oxidizing agents

10.6 Hazardous decomposition products:

In case of fire arise: smoke and carbon oxides. Under certain fire conditions tracks of other toxic products can not be excluded.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
 Acute toxicity Based on available data, the classification criteria are not met.
 LD/LC50 values relevant for classification:
 The quoted data are literature values and/or manufacturer/supplier data.

Specific symptoms in biological assay:

Skin corrosion/irritation

Based on available data, the classification criteria are not met. Repeated exposure may cause skin dryness or cracking.

Serious eye damage/irritation

Splashes of solvent may cause irritation to the eye and reversible damage. Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met. **Germ cell mutagenicity** Based on available data, the classification criteria are not met.

(Contd. on page 8)

⁻ DE/EN -



according to Regulation (EC) No 1907/2006, Article 31

Printing date 07.02.2025

Version number 06-02 (replaces version 06-01)

Revision: 07.02.2025

(Contd. of page 7)

Trade name: LUCITE® 123 All-Top Satin

Carcinogenicity Based on available data, the classification criteria are not met. **Reproductive toxicity** Based on available data, the classification criteria are not met.

STOT-single exposure Based on available data, the classification criteria are not met.

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard

Due to the viscosity (see section 9), classification as an aspiration hazard is omitted. Based on available data, the classification criteria are not met.

General notes:

Inhalation of solvent concentrations in excess of the OEL or MAK limit values can lead to health damage such as irritation of the mucous membranes and respiratory tract, damage to the kidneys and liver, and impairment of the central nervous system. Symptoms: headaches, dizziness, fatigue, muscle weakness, narcotic effect and, in exceptional cases, loss of consciousness. Prolonged or repeated contact with the product impairs the skin's natural lipid replenishment and causes the skin to dry out. The product can enter the body through the skin. Splashes of solvent may cause irritation to the eye and reversible damage.

Additional toxicological information:

CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

The product is not classified as carcinogenic, mutagenic or toxic to reproduction (CMR properties). **11.2 Information on other hazards**

Endocrin	e disrupting properties	
540-97-6	Dodecamethylcyclohexasiloxane	List II
541-02-6	Decamethylcyclopentasiloxane	List II
556-67-2	octamethylcyclotetrasiloxane	List II; III

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity: There are no st	atements/information available of the preparation	on.
12.2 Persistence and degradabi	ility	
Hydrocarbons, C10-C13, n-alka	nes, isoalkanes, cyclics, < 2% aromatics	
OECD 301F Manometric Respiro		
	readily biodegradable	
Hydrocarbons, C9-C11, n-alkan	es, isoalkanes, cyclics, < 2% aromatics	
Biodegradation	80 % (28d)	
	readily biodegradable	
12.3 Bioaccumulative potential		
Hydrocarbons, C9-C11, n-alkan	es, isoalkanes, cyclics, < 2% aromatics	
Partition Coefficient log Pow 5-6.	7 (n-octanol/water)	
12.4 Mobility in soil No further re	elevant information available.	
		(Contd. on page 9)

Page 9/11



Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 07.02.2025

Version number 06-02 (replaces version 06-01)

Revision: 07.02.2025

(Contd. of page 8)

Trade name: LUCITE® 123 All-Top Satin

12.5 Results of PBT and vPvB assessment

This product does not contain relevant substances that have been assessed as persistent, bioaccumulative and toxic (PBT) or as very persistent and very bioaccumulative (vPvB).

PBT: Not applicable.

vPvB: Not applicable.

12.6 Endocrine disrupting properties For information on endocrine disrupting properties see section 11.

12.7 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system. Must be specially treated adhering to official regulations.

European waste catalogue

08 01 11* waste paint and varnish containing organic solvents or other hazardous substances

14.1 UN number or ID number		
ADR, ADN, IMDG, IATA	Void	
14.2 UN proper shipping name		
ADR, ADN, IMDG, IATA	Void	
14.3 Transport hazard class(es)		
ADR, ADN, IMDG, IATA		
Class	Void	
14.4 Packing group		
ADR, IMDG, IATA	Void	
14.5 Environmental hazards:	Not applicable.	
14.6 Special precautions for user	Not applicable.	
14.7 Maritime transport in bulk according	g to IMO	
instruments	Not applicable.	

(Contd. on page 10)



according to Regulation (EC) No 1907/2006, Article 31

Printing date 07.02.2025

Version number 06-02 (replaces version 06-01)

Revision: 07.02.2025

Trade name: LUCITE® 123 All-Top Satin

(Contd. of page 9)

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

REGULATION (EU) 2019/1148

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

National regulations:

Information about limitation of use:

Observe employment restrictions concerning young persons.

Observe employment restrictions for expectant or nursing mothers.

Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.

Labelling according to Regulation (EC) No 2004/42

VOC limit according to 2004/42/EC for category d (SB) and maximum VOC content: see lid.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

The given conditions of work of the user extract themselves from our knowledge and control. The product/the preparation may be used without written permission for no other use, than the mentioned intended purpose. The user is responsible for the observance of all necessary legal instructions.

This Safety Data Sheet replaces all previous versions. With the newest version in each case, the preceding Safety Data Sheets are set out of strength.

For further information please consult the "Technical Data Sheet". Misuse may cause damage to health and environment.

(Contd. on page 11)

Page 11/11



Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 07.02.2025

Version number 06-02 (replaces version 06-01)

Revision: 07.02.2025

Trade name: LUCITE® 123 All-Top Satin

Labelling according to regulation (EC) No 528/2012Additional information:Safety data sheet available on request.Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.Wording of H and EUH phrases (number and full text)H226Flammable liquid and vapour.H302Harmful if swallowed.H304May be fatal if swallowed and enters airways.H332Harmful if inhaled.H336May cause drowsiness or dizziness.H351Suspected of causing cancer.H361fdSuspected of damaging fertility. Suspected of damaging the unborn child.EUH066Repeated exposure may cause skin dryness or cracking.Date of previous version: 04.06.2024Version number of previous version: 06-01Abbreviations and acronyms:Flam. Liq. 3: Flammable liquid – Category 3Acute Tox. 4: Acute toxicity – Category 2Repr. 2: Reproductive toxicity – Category 2STOT SE 3: Specific target organ toxicity (single exposure) – Category 3Asp. Tox. 1: Aspiration hazard – Category 1* Data compared to the previous version altered.		(Contd. of pa	ge
Safety data sheet available on request. Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. Wording of H and EUH phrases (number and full text) H226 Flammable liquid and vapour. H302 Harmful if swallowed. H304 May be fatal if swallowed and enters airways. H332 Harmful if inhaled. H336 May cause drowsiness or dizziness. H351 Suspected of causing cancer. H361fd Suspected of damaging fertility. Suspected of damaging the unborn child. EUH066 Repeated exposure may cause skin dryness or cracking. Date of previous version: 04.06.2024 Version number of previous version: 06-01 Abbreviations and acronyms: Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 4: Acute toxicity – Category 2 Repr. 2: Reproductive toxicity – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 Asp. Tox. 1: Aspiration hazard – Category 1	Labellin	ig according to regulation (EC) No 528/2012	
 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. Wording of H and EUH phrases (number and full text) H226 Flammable liquid and vapour. H302 Harmful if swallowed. H304 May be fatal if swallowed and enters airways. H332 Harmful if inhaled. H336 May cause drowsiness or dizziness. H351 Suspected of causing cancer. H361fd Suspected of damaging fertility. Suspected of damaging the unborn child. EUH066 Repeated exposure may cause skin dryness or cracking. Date of previous version: 04.06.2024 Version number of previous version: 06-01 Abbreviations and acronyms: Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 4: Acute toxicity – Category 2 Rep. 2: Reproductive toxicity – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 Asp. Tox. 1: Aspiration hazard – Category 1 	Additio	nal information:	
 Wording of H and EUH phrases (number and full text) H226 Flammable liquid and vapour. H302 Harmful if swallowed. H304 May be fatal if swallowed and enters airways. H332 Harmful if inhaled. H336 May cause drowsiness or dizziness. H351 Suspected of causing cancer. H361fd Suspected of damaging fertility. Suspected of damaging the unborn child. EUH066 Repeated exposure may cause skin dryness or cracking. Date of previous version: 04.06.2024 Version number of previous version: 06-01 Abbreviations and acronyms: Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 4: Acute toxicity – Category 4 Carc. 2: Carcinogenicity – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 Asp. Tox. 1: Aspiration hazard – Category 1 	Safety d	ata sheet available on request.	
 Wording of H and EUH phrases (number and full text) H226 Flammable liquid and vapour. H302 Harmful if swallowed. H304 May be fatal if swallowed and enters airways. H332 Harmful if inhaled. H336 May cause drowsiness or dizziness. H351 Suspected of causing cancer. H361fd Suspected of damaging fertility. Suspected of damaging the unborn child. EUH066 Repeated exposure may cause skin dryness or cracking. Date of previous version: 04.06.2024 Version number of previous version: 06-01 Abbreviations and acronyms: Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 4: Acute toxicity – Category 4 Carc. 2: Carcinogenicity – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 Asp. Tox. 1: Aspiration hazard – Category 1 			
 H226 Flammable liquid and vapour. H302 Harmful if swallowed. H304 May be fatal if swallowed and enters airways. H332 Harmful if inhaled. H336 May cause drowsiness or dizziness. H351 Suspected of causing cancer. H361fd Suspected of damaging fertility. Suspected of damaging the unborn child. EUH066 Repeated exposure may cause skin dryness or cracking. Date of previous version: 04.06.2024 Version number of previous version: 06-01 Abbreviations and acronyms: Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 4: Acute toxicity – Category 4 Carc. 2: Carcinogenicity – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 Asp. Tox. 1: Aspiration hazard – Category 1 	-		
 Harmful if swallowed. Hay be fatal if swallowed and enters airways. Hay be fatal if swallowed and enters airways. Hay cause drowsiness or dizziness. Hay cause drowsiness or dizziness. Suspected of causing cancer. Haeffd Suspected of damaging fertility. Suspected of damaging the unborn child. EUH066 Repeated exposure may cause skin dryness or cracking. Date of previous version: 04.06.2024 Version number of previous version: 06-01 Abbreviations and acronyms: Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 4: Acute toxicity – Category 4 Carc. 2: Carcinogenicity – Category 2 Repr. 2: Reproductive toxicity – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 Asp. Tox. 1: Aspiration hazard – Category 1 			
 Harmful if inhaled. H336 May cause drowsiness or dizziness. H351 Suspected of causing cancer. H361fd Suspected of damaging fertility. Suspected of damaging the unborn child. EUH066 Repeated exposure may cause skin dryness or cracking. Date of previous version: 04.06.2024 Version number of previous version: 06-01 Abbreviations and acronyms: Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 4: Acute toxicity – Category 4 Carc. 2: Carcinogenicity – Category 2 Repr. 2: Reproductive toxicity – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 Asp. Tox. 1: Aspiration hazard – Category 1 	H302		
 Harmful if inhaled. H336 May cause drowsiness or dizziness. H351 Suspected of causing cancer. H361fd Suspected of damaging fertility. Suspected of damaging the unborn child. EUH066 Repeated exposure may cause skin dryness or cracking. Date of previous version: 04.06.2024 Version number of previous version: 06-01 Abbreviations and acronyms: Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 4: Acute toxicity – Category 4 Carc. 2: Carcinogenicity – Category 2 Repr. 2: Reproductive toxicity – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 Asp. Tox. 1: Aspiration hazard – Category 1 		May be fatal if swallowed and enters airways.	
 H351 Suspected of causing cancer. H361fd Suspected of damaging fertility. Suspected of damaging the unborn child. EUH066 Repeated exposure may cause skin dryness or cracking. Date of previous version: 04.06.2024 Version number of previous version: 06-01 Abbreviations and acronyms: Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 4: Acute toxicity – Category 4 Carc. 2: Carcinogenicity – Category 2 Repr. 2: Reproductive toxicity – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 Asp. Tox. 1: Aspiration hazard – Category 1 	H332		
 H351 Suspected of causing cancer. H361fd Suspected of damaging fertility. Suspected of damaging the unborn child. EUH066 Repeated exposure may cause skin dryness or cracking. Date of previous version: 04.06.2024 Version number of previous version: 06-01 Abbreviations and acronyms: Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 4: Acute toxicity – Category 4 Carc. 2: Carcinogenicity – Category 2 Repr. 2: Reproductive toxicity – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 Asp. Tox. 1: Aspiration hazard – Category 1 	H336	May cause drowsiness or dizziness.	
 H361fd Suspected of damaging fertility. Suspected of damaging the unborn child. EUH066 Repeated exposure may cause skin dryness or cracking. Date of previous version: 04.06.2024 Version number of previous version: 06-01 Abbreviations and acronyms: Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 4: Acute toxicity – Category 4 Carc. 2: Carcinogenicity – Category 2 Repr. 2: Reproductive toxicity – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 Asp. Tox. 1: Aspiration hazard – Category 1 	H351	•	
EUH066 Repeated exposure may cause skin dryness or cracking. Date of previous version: 04.06.2024 Version number of previous version: 06-01 Abbreviations and acronyms: Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 4: Acute toxicity – Category 4 Carc. 2: Carcinogenicity – Category 2 Repr. 2: Reproductive toxicity – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 Asp. Tox. 1: Aspiration hazard – Category 1	H361fd		
Date of previous version: 04.06.2024 Version number of previous version: 06-01 Abbreviations and acronyms: Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 4: Acute toxicity – Category 4 Carc. 2: Carcinogenicity – Category 2 Repr. 2: Reproductive toxicity – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 Asp. Tox. 1: Aspiration hazard – Category 1			
Version number of previous version: 06-01 Abbreviations and acronyms: Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 4: Acute toxicity – Category 4 Carc. 2: Carcinogenicity – Category 2 Repr. 2: Reproductive toxicity – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 Asp. Tox. 1: Aspiration hazard – Category 1	Date of	previous version: 04.06.2024	
Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 4: Acute toxicity – Category 4 Carc. 2: Carcinogenicity – Category 2 Repr. 2: Reproductive toxicity – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 Asp. Tox. 1: Aspiration hazard – Category 1		•	
Acute Tox. 4: Acute toxicity – Category 4 Carc. 2: Carcinogenicity – Category 2 Repr. 2: Reproductive toxicity – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 Asp. Tox. 1: Aspiration hazard – Category 1	Abbrevi	ations and acronyms:	
Carc. 2: Carcinogenicity – Category 2 Repr. 2: Reproductive toxicity – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 Asp. Tox. 1: Aspiration hazard – Category 1	Flam. Liq.	3: Flammable liquids – Category 3	
Repr. 2: Reproductive toxicity – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 Asp. Tox. 1: Aspiration hazard – Category 1			
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 Asp. Tox. 1: Aspiration hazard – Category 1			
Asp. Tox. 1: Aspiration hazard – Category 1	•		
* Data compared to the previous version altered.			
	* Data c	ompared to the previous version altered.	