

Revision: 11.02.2025

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.02.2025 Version number 04-04 (replaces version 04-03)

CECTION 4. Identification of the authoroughly form and of the appropriately inc

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: LUCITE® 124 1K-PU Color Satin

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture Coating agent

Uses advised against

This product is not suitable for uses other than those specified in the "Use of the substance/mixture". If your particular manner of use is not listed, please contact the creator of this safety data sheet.

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Dörken Coatings GmbH & Co. KG

Wetterstr. 58 58313 Herdecke

Germany

www.doerkencoatings.de

Phone: +49 2330 63 243 Fax: +49 2330 63 100 243

Further information obtainable from: msds.coatings@doerken.de

1.4 Emergency telephone number:

Emergency CONTACT (24-Hour-Number):

GBK GmbH +49 (0)6132-84463

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

The product is not classified, according to the CLP regulation.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 Void

Hazard pictograms Void

Signal word Void

Hazard statements Void

Additional information:

EUH208 Contains mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1),

 $1, 2-benzis othiazol-3 (2H)-one,\ 2,4,7,9-tetramethyldec-5-yne-4,7-diol,\ 2,4,7,9-Te$

4,7-diol, ethoxylated (1 - 4.5 moles ethoxylated). May produce an allergic reaction.

EUH210 Safety data sheet available on request.

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable.

(Contd. on page 2)



according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.02.2025 Version number 04-04 (replaces version 04-03) Revision: 11.02.2025

Trade name: LUCITE® 124 1K-PU Color Satin

vPvB: Not applicable.

(Contd. of page 1)

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

CAS: 13463-67-7	Titanium dioxide	10-25%
EINECS: 236-675-5 Reg.nr.: 01-2119489379-17-xxxx	Carc. 2, H351	10-2070
CAS: 34590-94-8 EINECS: 252-104-2 Reg.nr.: 01-2119450011-60-xxxx	Dipropylene glycol monomethyl ether substance with a Community workplace exposure limit	<2.5%
CAS: 126-86-3 EINECS: 204-809-1 Reg.nr.: 01-2119954390-39-xxxx	2,4,7,9-tetramethyldec-5-yne-4,7-diol Eye Dam. 1, H318; Skin Sens. 1B, H317; Aquatic Chronic 3, H412	≥0.1-<1%
CAS: 9014-85-1 NLP: 500-022-5 Reg.nr.: 01-2119954393-33-xxxx	2,4,7,9-Tetramethyldec-5-yne-4,7-diol, ethoxylated (1 - 4.5 moles ethoxylated) Eye Dam. 1, H318; Skin Sens. 1B, H317; Aquatic Chronic 3, H412	≥0.1-<0.25%
CAS: 77-99-6 EINECS: 201-074-9 Reg.nr.: 01-2119486799-10-xxxx	propylidynetrimethanol Repr. 2, H361fd	<0.25%
CAS: 2634-33-5 EINECS: 220-120-9 Reg.nr.: 01-2120761540-60-xxxx	1,2-benzisothiazol-3(2H)-one Acute Tox. 2, H330; Eye Dam. 1, H318; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Acute Tox. 4, H302; Skin Irrit. 2, H315; Skin Sens. 1, H317 Specific concentration limit: Skin Sens. 1; H317: C≥ 0.05 %	≥0.025-<0.05%
CAS: 55965-84-9 Reg.nr.: 01-2120764691-48-xxxx	mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) Acute Tox. 3, H301; Acute Tox. 2, H310; Acute Tox. 2, H330; Skin Corr. 1C, H314; Eye Dam. 1, H318; Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410 (M=100); Skin Sens. 1A, H317, EUH071 Specific concentration limits: Skin Corr. 1C; H314:C \geq 0.6 % Skin Irrit. 2; H315: 0.06 % \leq C < 0.6 % Eye Dam. 1; H318: C \geq 0.6 % Eye Irrit. 2; H319: 0.06 % \leq C < 0.6 % Skin Sens. 1A; H317: C \geq 0.0015 %	≥0.00025-<0.0015

- DE/EN



according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.02.2025 Version number 04-04 (replaces version 04-03) Revision: 11.02.2025

Trade name: LUCITE® 124 1K-PU Color Satin

(Contd. of page 2)

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information:

In all cases of doubt, or when symptoms persist, seek medical advice.

Soiled, soaked clothes immediately take off.

Never give anything by mouth to an unconscious person.

After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact:

Wash with plenty of soap and water.

In case of skin reactions consult a physician. Do not scratch.

After eye contact:

Remove contact lenses. Keep eye lids open and rinse plentifully for at least 10 minutes with clean running water. Subsequently consult an ophthalmologist.

In case of troubles or persistent symptoms, consult an opthalmologist.

After swallowing:

Rinse out mouth and then drink plenty of water.

Seek immediate medical advice.

4.2 Most important symptoms and effects, both acute and delayed Allergic reactions

4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents:

Extinguishing powder, foam, carbon dioxide.

Use fire extinguishing methods suitable to surrounding conditions.

For safety reasons unsuitable extinguishing agents: Water with full jet

5.2 Special hazards arising from the substance or mixture

Fire will produce dangerous decomposition products like dense, black smoke, carbon dioxide (CO₂), carbon monoxide (CO) and nitrogen oxides (NOx). Inhalation may cause serious health damage.

Under certain fire conditions, traces of other toxic gases cannot be excluded.

5.3 Advice for firefighters

Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

Additional information

Collect contaminated fire fighting water separately. It must not enter the sewage system.

DE/EN



according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.02.2025 Version number 04-04 (replaces version 04-03) Revision: 11.02.2025

Trade name: LUCITE® 124 1K-PU Color Satin

(Contd. of page 3)

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Avoid contact with skin and eyes.

6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Keep contaminated washing water and dispose of appropriately.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose of the material collected according to regulations.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Avoid prolonged, intensive skin contact and contact with the eyes.

Avoid the handling of incompatible substances and mixtures. Incompatible substances: see section 10.5

Information about fire - and explosion protection: No special measures required.

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles:

Make sure spills can be contained, e.g. in sump pallets.

Protect from frost, heat and direct sunlight. Keep tightly closed, cool and dry.

Information about storage in one common storage facility:

Note the rules for common storage in accordance with TRGS 510 - "Storage of hazardous substances in transportable containers".

Store away from foodstuffs.

Further information about storage conditions: None.

Storage class: 12

7.3 Specific end use(s) No further relevant information available.

DE/EN

(Contd. on page 5)



according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.02.2025 Version number 04-04 (replaces version 04-03) Revision: 11.02.2025

Trade name: LUCITE® 124 1K-PU Color Satin

(Contd. of page 4)

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:					
57-55-6 Propyler	57-55-6 Propylene glycol				
MAK (Germany)	als Dampf und Aerosol;vgl.Abschn.IIb und Xc				
34590-94-8 Dipro	34590-94-8 Dipropylene glycol monomethyl ether				
AGW (Germany)	Long-term value: 310 mg/m³, 50 ppm 1(I);DFG, EU, 11				
IOELV (EU)	Long-term value: 308 mg/m³, 50 ppm Skin				
55965-84-9 mixt	55965-84-9 mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)				
MAK (Germany)	Long-term value: 0.2E mg/m³ vgl.Abschn.Xc				

Regulatory information

AGW (Germany): TRGS 900 IOELV (EU): (EU) 2019/1831

Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls Provide good ventilation and/or an exhaust system in the work area.

Appropriate engineering controls

Ensure a good ventilation. This can be achieved by local exhaustion or general exhaust air.

Individual protection measures, such as personal protective equipment General protective and hygienic measures:

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Immediately remove all soiled and contaminated clothing

Do not eat, drink, smoke or sniff while working.

Use skin protection cream for skin protection.

Respiratory protection:

Breathing protection is always required when spraying. Use combination filter A2(-P2) according to EN 14387.

Hand protection

Material of gloves

Nitrile rubber

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 6)



according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.02.2025 Version number 04-04 (replaces version 04-03) Revision: 11.02.2025

Trade name: LUCITE® 124 1K-PU Color Satin

(Contd. of page 5)

Eye/face protection

Wear protective goggles to protect against splashing.

Professional Cooperative Rules - BGR 192 Use of eye and face protection

Body protection: Impervious protective clothing

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Physical state Fluid

Colour: Different according to colouring

Odour: Weak after glycol ethers

Odour threshold: Not applicable for mixtures.

Melting point/Freezing point: Not security-related.

Boiling point or initial boiling point and boiling

range 100 °C (7732-18-5 water)

Flammability Not applicable.

Lower and upper explosion limit

Lower:Not determined.Upper:Not determined.Flash point:Not applicable.Auto-ignition temperature:Not applicable.

Decomposition temperature: For mixtures not applicable.

pH at 20 °C 7.5-9

Viscosity: Not security-related.

Solubility

water: Miscible / waterdilutable.

polar solvents: Partly miscible.

non-polar solvents:

Partition coefficient n-octanol/water (log value)

Vapour pressure at 20 °C:

Not miscible or difficult to mix.

For mixtures not applicable.
23 hPa (7732-18-5 water)

Density and/or relative density

Density at 20 °C: 1.02-1.29 g/cm³ **Vapour density** Not applicable.

9.2 Other information

Appearance:

Form: Fluid

Important information on protection of health and

environment, and on safety.

Ignition temperature: Product is not selfigniting.

Explosive properties: Product does not present an explosion hazard.

(Contd. on page 7)



according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.02.2025 Version number 04-04 (replaces version 04-03) Revision: 11.02.2025

Trade name: LUCITE® 124 1K-PU Color Satin

(Contd. of page 6)

Change in condition Softening point/range Oxidising properties

In its condition as supplied, the product is neither

flammable nor oxidising.

Evaporation rate For mixtures not applicable.

Information with regard to physical hazard

classes **Explosives** Void Void Flammable gases **Aerosols** Void Oxidising gases Void Gases under pressure Void Flammable liquids Void Flammable solids Void Self-reactive substances and mixtures Void **Pyrophoric liquids** Void Pyrophoric solids Void Self-heating substances and mixtures Void Substances and mixtures, which emit flammable gases in contact with water Void Oxidising liquids Void **Oxidising solids** Void Organic peroxides Void **Corrosive to metals** Void **Desensitised explosives** Void

SECTION 10: Stability and reactivity

- 10.1 Reactivity No further relevant information available.
- **10.2 Chemical stability** Product is stable under normal storage conditions.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: strong oxidizing agents
- 10.6 Hazardous decomposition products:

In case of fire arise: smoke and carbon oxides. Under certain fire conditions tracks of other toxic products can not be excluded.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:

The quoted data are literature values and/or manufacturer/supplier data.

(Contd. on page 8)



according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.02.2025 Version number 04-04 (replaces version 04-03) Revision: 11.02.2025

Trade name: LUCITE® 124 1K-PU Color Satin

(Contd. of page 7)

Specific symptoms in biological assay:

Skin corrosion/irritation Based on available data, the classification criteria are not met.

Serious eye damage/irritation Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure Based on available data, the classification criteria are not met.

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

Additional toxicological information:

CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

The product is not classified as carcinogenic, mutagenic or toxic to reproduction (CMR properties).

11.2 Information on other hazards

Endocrine disrupting properties		
556-67-2	octamethylcyclotetrasiloxane	List II; III
541-02-6	Decamethylcyclopentasiloxane	List II
540-97-6	Dodecamethylcyclohexasiloxane	List II

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity: There are no statements/information available of the preparation.

- 12.2 Persistence and degradability No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.

12.5 Results of PBT and vPvB assessment

This product does not contain relevant substances that have been assessed as persistent, bioaccumulative and toxic (PBT) or as very persistent and very bioaccumulative (vPvB).

PBT: Not applicable. **vPvB:** Not applicable.

12.6 Endocrine disrupting properties For information on endocrine disrupting properties see section 11.

12.7 Other adverse effects No further relevant information available.

DE/EN

(Contd. on page 9)



according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.02.2025 Version number 04-04 (replaces version 04-03) Revision: 11.02.2025

Trade name: LUCITE® 124 1K-PU Color Satin

(Contd. of page 8)

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system. Must be specially treated adhering to official regulations.

European waste catalogue

08 01 12 waste paint and varnish other than those mentioned in 08 01 11

14.1 UN number or ID number		
ADR, ADN, IMDG, IATA	Void	
14.2 UN proper shipping name		
ADR, ADN, IMDG, IATA	Void	
14.3 Transport hazard class(es)		
ADR, ADN, IMDG, IATA		
Class	Void	
14.4 Packing group		
ADR, IMDG, IATA	Void	
14.5 Environmental hazards:	Not applicable.	
14.6 Special precautions for user	Not applicable.	
14.7 Maritime transport in bulk according	g to IMO	
instruments	Not applicable.	
UN "Model Regulation":	Void	

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

(Contd. on page 10)



according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.02.2025 Version number 04-04 (replaces version 04-03) Revision: 11.02.2025

Trade name: LUCITE® 124 1K-PU Color Satin

(Contd. of page 9)

REGULATION (EU) 2019/1148

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

National regulations:

Information about limitation of use:

Observe employment restrictions concerning young persons.

Observe employment restrictions for expectant or nursing mothers.

Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.

Labelling according to Regulation (EC) No 2004/42

VOC limit according to 2004/42/EC for category d (WB) and maximum VOC content: see lid.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

The given conditions of work of the user extract themselves from our knowledge and control. The product/the preparation may be used without written permission for no other use, than the mentioned intended purpose. The user is responsible for the observance of all necessary legal instructions.

This Safety Data Sheet replaces all previous versions. With the newest version in each case, the preceding Safety Data Sheets are set out of strength.

For further information please consult the "Technical Data Sheet".

Misuse may cause damage to health and environment.

Labelling according to regulation (EC) No 528/2012

Additional information:

Contains protective agent for products in storage.

Contains mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1), 1,2-benzisothiazol-3(2H)-one, 2,4,7,9-tetramethyldec-5-yne-4,7-diol, 2,4,7,9-Tetramethyldec-5-yne-4,7-diol, ethoxylated (1 - 4.5 moles ethoxylated). May produce an allergic reaction.

Safety data sheet available on request.

Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Wording of H and EUH phrases (number and full text)

H301 Toxic if swallowed.

H302 Harmful if swallowed.

(Contd. on page 11)



according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.02.2025 Version number 04-04 (replaces version 04-03) Revision: 11.02.2025

Trade name: LUCITE® 124 1K-PU Color Satin

		(Contd. of page 10)
H310	Fatal in contact with skin.	
H314	Causes severe skin burns and eye damage.	
H315	Causes skin irritation.	
H317	May cause an allergic skin reaction.	
H318	Causes serious eye damage.	
H319	Causes serious eye irritation.	
H330	Fatal if inhaled.	
H351	Suspected of causing cancer.	
H361fd	Suspected of damaging fertility. Suspected of damaging the unborn child.	
H400	Very toxic to aquatic life.	
H410	Very toxic to aquatic life with long lasting effects.	
H412	Harmful to aquatic life with long lasting effects.	
	Corrosive to the respiratory tract.	
	previous version: 23.01.2024	
	number of previous version: 04-03	
Abbrevi	ations and acronyms:	
	. 3: Acute toxicity – Category 3	
Acute Tox	. 4: Acute toxicity – Category 4	
	. 2: Acute toxicity – Category 2	
	1C: Skin corrosion/irritation – Category 1C	
	2: Skin corrosion/irritation – Category 2 1: Serious eye damage/eye irritation – Category 1	
	. 1: Skin sensitisation – Category 1	
	. 1A: Skin sensitisation – Category 1A	
	. 1B: Skin sensitisation – Category 1B	
	arcinogenicity – Category 2	
•	eproductive toxicity – Category 2	
	cute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1 hronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1	
	hronic 3: Hazardous to the aquatic environment - long-term aquatic hazard — Category 3	
•	ompared to the previous version altered.	
	•	

DE/EN